

Attorney Docket No.: 22674-7021

PATENT APPLICATION

Integrated Color LED Chip

Inventor: Larry Ragle
3188 Stelling Drive
Palo Alto, CA 94303
A Citizen of the United States of America

Assignee: The Fox Group, Inc.
2021 Las Positas Court #113
Livermore, California 94550

Entity: Small

McCutchen, Doyle, Brown & Enersen LLP
Three Embarcadero Center, Suite 2500
San Francisco, California 94111
(415) 393-2000

Integrated Color LED Chip

5 CROSS-REFERENCES TO RELATED APPLICATIONS

This application claims benefit from Provisional Application Serial No. 60/214,505, filed June 28, 2000.

FIELD OF THE INVENTION

10 The present invention relates generally to multicolor display devices and, more particularly, to a method and apparatus for achieving multiple colors on an integrated chip.

BACKGROUND OF THE INVENTION

15 Multicolor generation systems are used in a variety of applications including monitors (e.g., direct and projection televisions, computer monitors), macro-displays (e.g., billboards), and micro-displays (e.g., telephones and PDAs). Currently a number of different techniques are used to achieve multicolor displays. For example, depending upon application requirements such as contrast, brightness, color range, color accuracy, power consumption, size and cost, a display may utilize light generation systems based on everything from CRTs to LCDs.

20 Currently, the emphasis on full-featured microelectronic systems has resulted in manufacturers working to develop more efficient, multicolor displays that can replace the simple monotone displays common in such devices. Although LCD display based systems have proven adequate for some applications, device complexity and cost have prohibited their use for the majority of such systems. The present invention
25 overcomes the obstacles associated with the prior approaches and provides a simple display device that can be tailored to meet varying color and display size requirements.

SUMMARY OF THE INVENTION

30 The present invention provides a method and apparatus for achieving multicolor displays using an integrated color chip. The integrated color chip contains one or more multicolor generation sites on a single substrate. Each multicolor generation site



is comprised of two or more light emitting regions, preferably LEDs, in close enough proximity to one another to achieve color integration. The active light generation system for each light emitting region, e.g., an LED, is preferably identical in device structure although size and shape may vary. In order to achieve the desired-colors, one or more light conversion layers are applied to individual light emitting regions. Thus, for example, a simple three color generation site may include three blue light emitting LEDs, one of which includes a blue-to-green light conversion layer and one of which includes a blue-to-red light conversion layer. Each light emitting region may also include index matching layers, preferably interposed between the outermost surface of the light emitter and the light conversion layer, and protective layers.

The number of required light emitting regions per multicolor generation site depends upon the application. For example, a two color system comprised of a blue color emitting region and a yellow color emitting region can be used to produce a range of colors, including white. Alternately, a complete color range can be achieved using a three color system comprised of three light emitting regions. Preferably the three light emitting regions in combination with the required light conversion layers emit three primary additives such as red light, green light, and blue light.

In at least one embodiment of the invention, opaque material is deposited between adjacent light emitting regions thereby minimizing cross-talk and achieving improved contrast. In at least one other embodiment of the invention, cross-talk due to substrate reflections is minimized by removing the light emitting regions from the substrate on which they were grown and affixing them to a secondary, support substrate. In at least one other embodiment of the invention, cross-talk due to substrate reflections is minimized by interposing an absorbing or partially reflective material between the substrate and the light emitting regions.

A further understanding of the nature and advantages of the present invention may be realized by reference to the remaining portions of the specification and the drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a top view of an embodiment of the invention comprised of a three color integrated color chip;



Fig. 2 is a top view of an alternate embodiment of the invention with an improved emitter packing density;

Fig. 3 is a top view of an alternate embodiment of the invention in which the light emitting regions are of different dimensions to compensate for variations in perceived light intensity;

Fig. 4 is a cross-sectional view of an embodiment of the invention;

Fig. 5 is a cross-sectional view of an alternate embodiment of the invention;

Fig. 6 is an illustration of an integrated color chip containing a plurality of multicolor sites;

Fig. 7 illustrates cross-talk between adjacent light emitting regions;

Fig. 8 illustrates one method of isolating adjacent light emitting regions;

Fig. 9 is a cross-sectional view taken along plane A-A of the embodiment shown in Fig. 8;

Fig. 10 is a cross-sectional view of an alternate method of minimizing cross-talk due to edge emissions;

Fig. 11 is a cross-sectional view of an embodiment of the invention designed to minimize cross-talk due to light emitted into the substrate;

Fig. 12 illustrates the first stage of an alternate approach to minimizing cross-talk between the individual light emitting regions of the invention;

Fig. 13 illustrates the second stage of an alternate approach to minimizing cross-talk between the individual light emitting regions of the invention;

Fig. 14 illustrates the third stage of an alternate approach to minimizing cross-talk between the individual light emitting regions of the invention; and

Fig. 15 illustrates the fourth stage of an alternate approach to minimizing cross-talk between the individual light emitting regions of the invention.

DESCRIPTION OF THE SPECIFIC EMBODIMENTS

Fig. 1 is an illustration of an embodiment of the invention. In the embodiment shown, an integrated color chip (ICC) 100 contains a single set of color emitting regions 101-103 residing on a single substrate 105 (e.g., a substrate comprised of sapphire, silicon carbide, gallium nitride, etc.). Preferably light emitting regions 101-103 are in sufficiently close proximity to one another to facilitate color integration by an

observer. It will be understood that as the apparent distance between ICC 100 and the observer increase, the required spacing between light emitting regions 101-103 increases. Although each light emitting region 101-103 is illustrated as having a circular shape, it is understood that the inventor envisions other shapes. For example, as shown in Fig. 2, light emitting regions 201-203 are non-circular in order to achieve improved packing density. Alternately, as shown in Fig. 3, light emitting regions 301-303 are of different dimensions, the dimensional variations compensating for variations in perceived light intensity from the different emitting regions, thus achieving a balanced output.

In the preferred embodiment of the invention, each individual light emitting region (e.g., regions 101-103, 201-203, and 301-303) is comprised of a light emitting diode (LED) and, as required to achieve the desired color, a color (i.e., wavelength) conversion layer (e.g., one or more phosphor and/or active polymer layers). Preferably the LEDs emit violet or blue light (i.e., in the wavelength range of between 4,000 and 4,912 Angstroms) although it is understood that the invention can utilize other wavelength LEDs. The LED structures can be manufactured using a variety of fabrication techniques that are well known by those of skill in the art. In the preferred embodiment of the invention, the LED structures are grown on substrate 105 using the HVPE techniques disclosed in pending U.S. Patent Application Serial No. 09/861,011, pages 7-15, the teachings of which are hereby incorporated by reference. However, other device manufacturing techniques such as MOCVD and MBE can also be used to fabricate the LED structures of the present invention.

Assuming that the LED structures emit blue light, only two of the three light emitting regions require color conversion layers in order to achieve a tristimulus color space that can be used to generate any desired color. For example and as illustrated in Fig. 4, by applying a conversion layer 401 to light emitting region 101 to down frequency convert the emitted blue light to green light (i.e., in the wavelength range of between 4,912 and 5,750 Angstroms), and applying a conversion layer 403 to light emitting region 103 to down frequency convert the emitted blue light to red light (i.e., in the wavelength range of between 6,470 and 7,000 Angstroms), the standard set of additive primaries can be generated (i.e., red, green and blue or RGB). It is understood that the invention can also be used to generate non-RGB light emissions for a variety of applications, some of which do not require the ability to generate all colors. For example,



the invention can be used to generate a subset of the visible colors with only two light emitting regions.

The light converting coatings, for example blue-to-green layer 401 and blue-to-red layer 403, are preferably deposited onto the designated light emitting regions using standard coating techniques as are well known by those of skill in the art. For example, the first conversion layer (e.g., layer 401) can be deposited by spraying or spin coating followed by a curing step. Once cured, the coating is selectively removed by standard photolithographic techniques so that only predetermined light emitting regions (or region for a structure comprised of only three light emitting regions) are covered by the conversion layer. The same process is then used to coat the second conversion layer (e.g., layer 403). It is understood that a variety of other well known techniques can be used to deposit the desired light conversion layers. For example, a masking system can be used to selectively coat predetermined light emitting regions, the masking system used in conjunction with a liquid, evaporative, or other coating technique. Alternately, an automated, microrobotic drop dispenser can be used to deposit the conversion layers on each of the designated light emitting regions.

Preferably an index of refraction matching layer 501 is interposed between light emitting region 101 and light converting coating 401 and an index of refraction matching layer 503 is interposed between light emitting region 103 and light converting coating 403 as illustrated in Fig. 5. Matching layers 501 and 503 are selected from a class of transparent materials having an index of refraction between that of the underlying semiconductor material and that of the overlying light conversion coating. The matching layers facilitate the definition of the conversion layers by planarizing or partially planarizing the light emitting regions prior to the application of the conversion layers. Matching layers 501 and 503 are preferably deposited using the same techniques used to deposit the conversion layers, thus simplifying the fabrication process.

In some embodiments of the invention, a protective layer 505 is deposited onto the device. Protective layer 505 provides an environmental sealant for the device and, more particularly, for the conversion layers. Additionally, layer 505 is preferably designed to provide an index of refraction matching layer to the ambient environment (e.g., air) and to provide lensing to converge the emitted light rays and project them away from the device's surface. As shown in Fig. 5, protective layer 505 covers all three light emitting regions although it is understood that the protective layer can be deposited on



only a portion of the device structure (e.g., only on the light conversion layers).

Preferably protective layer 505 is deposited using the same techniques as used with the conversion layers, thus simplifying the fabrication process.

5 In the preferred embodiment of the invention, a first contact 507 is located on the lower surface of substrate 105. A second contact is deposited on the upper surface of each light emitting region prior to the application of the index matching layers (e.g., 501 and 503), light conversion layers (e.g., 401 and 403), and/or any protective layers (e.g., 505). In the illustrated embodiment, contact 508 corresponds to light emitting region 101, contact 509 corresponds to light emitting region 102, and contact 510 corresponds to light emitting region 103.

10 A variety of techniques can be used to connect to the contacts located on the upper surfaces of the emitting regions. For example, after all of the desired coating layers are applied to the light emitting regions, a photoresist mask can be used in conjunction with an etching system to expose bonding areas (e.g., bonding pads) on each of the contacts (e.g., contacts 508-510). Alternately, laser ablation can be used to remove portions of the coating layers, thereby exposing bonding areas. Alternately, leads can be coupled to the contacts prior to the application of the coatings. Alternately, wrap-around contacts can be applied such that a portion of the contact wraps-around the edge of the light emitting regions. Leads can be coupled to the edge contacts prior to the application of the coatings or after subsequent exposure of the edge contacts by an etching or ablation technique. Alternately, after deposition of an insulating layer over the entire ICC and exposure of a bonding area on each contact, leads can be coupled to the contacts and connected to bonding regions on the edges of the ICC. In some embodiments, the insulating layer also acts as the index matching layer interposed between the light emitting regions and the light conversion layers. In other embodiments, the insulating layer is interposed between the light emitting regions and the index matching layer.

25 It is understood that the above-identified embodiments, for example the configurations illustrated in Figs. 1-3, are meant to be illustrative, and not limiting, of the invention. For example, the ICCs illustrated in these figures include only three light emitting regions per substrate. Fig. 6 illustrates a preferred embodiment of the invention in which a single substrate 601 includes a plurality of multicolor generation sites 603. Preferably each multicolor generation site 603 is comprised of three individual light emitting regions, at least two of which use color conversion layers as previously



described, although it is understood that each multicolor generation site 603 may be comprised of either fewer or greater numbers of individual light emitters. Additionally, it is understood that not all of the multicolor generation sites on a single substrate must be comprised of an equivalent number of individual light emitters.

5 Although the above-described embodiments provide multiple colors, improved contrast can be achieved by suppressing cross-talk between individual light emitting regions. The cross-talk phenomenon is illustrated in the cross-sectional view of a simplified device 700 provided in Fig. 7. As shown, two adjacent light emitting regions 701 and 703 are contained on a single substrate 105. Light emitting region 701 includes a
10 light conversion layer 705 and light emitting region 703 includes a light conversion layer 707. At a given time x , light emitting region 701 is activated. In addition to the light 709 emitted from the upper surface of 701, which passes through conversion layer 705, additional light is emitted from the side of region 701 (e.g., light 711) as well as the bottom surface of region 701 (e.g., light 713). A portion of the side emitted light 711 and,
15 to a lesser extent, bottom emitted light 713, may pass through adjacent region 703 and/or conversion layer 707. As a result, when one light emitting region is activated (e.g., 701) a portion of unintended light is emitted by the adjacent region (e.g., 703).

 In an embodiment of the invention illustrated in Fig. 8, a plurality of multicolor sites 801, each comprised of three light emitting regions 803, is
20 grown/deposited on a single substrate 805. It is understood that preferably adjacent light emitting regions 803 utilize different color conversion layers in order to achieve the desired multicolor system as described above. In the embodiment of the invention illustrated in Fig. 8 and further illustrated in Fig. 9, individual light emitting regions 803 are isolated from adjacent regions with an opaque material 807 (e.g., low temperature
25 glass, epoxy, or any of a variety of opaque organic materials). Opaque material 807 can be deposited, for example, using standard photolithographic coating techniques or any of a variety of other well known techniques such as a masking system used in conjunction with a liquid, evaporative, or other coating technique. In an alternate embodiment of the invention illustrated in Fig. 10, channels 1001 are formed between the light emitting
30 regions, for example using an ion etching or plasma etching system, prior to filling in the channels with opaque material 807.

 Although the embodiments illustrated in Figs. 8-10 aid in the elimination of cross-talk resulting from edge emissions, these embodiments do not significantly

impact cross-talk arising from light emitted into substrate 805 (e.g., light 713 shown in Fig. 7). One approach to minimizing cross-talk due to light emitted into the substrate is illustrated in Fig. 11. As shown, a layer 1101 is grown or deposited on the surface of substrate 1103 prior to the growth of light emitting regions 1105. Layer 1101 can be designed to be substantially absorbing, opaque, or reflective to certain wavelengths in order to minimize undesired substrate reflections. For example, layer 1101 can be a distributed Bragg reflector, preferably comprised of a three region stack optimized for the three wavelengths of interest (e.g., red, green and blue light). Preferably, as in the prior example, the area between adjacent regions 1105 is filled with opaque material 807. It is understood that light emitting regions 1105 include, as previously described, light conversion layers as required to achieve the desired wavelengths, contact structures, protective coatings (if desired) and index matching layers (if desired).

Figs. 12-15 illustrate an alternate approach to minimizing cross-talk between light emitting regions. During the first stage of device fabrication, illustrated in Fig. 12, light emitting regions 1201 are grown on substrate 1203. The order of the layers (e.g., the n-type and p-type layers) comprising regions 1201 is reversed from the desired final order. During the second stage of device fabrication, illustrated in Fig. 13, opaque material 1301 is deposited between adjacent regions 1201 in order to isolate the edges of the emitting regions. Additionally, the top surfaces of regions 1201 are coated with a contact layer 1303. Preferably contact layer 1303 is comprised of metal and is opaque to visible light, and more preferably reflective of visible light. During the third stage of device fabrication, illustrated in Fig. 14, a second substrate 1401 is coupled to the top surfaces of regions 1201, preferably via interposed contact layers 1303. The coupling surface of substrate 1401 may be conductive, thus allowing voltage to be simultaneously applied to one surface (e.g., contact layer 1303) of all emitting regions 1201. Alternately, substrate 1401 may include a plurality of leads that correspond to individual regions 1201 (e.g., individual contact layers 1303), thus allowing voltage to be applied selectively to regions 1201. In the last stage of device fabrication, illustrated in Fig. 15, substrate 1203 is removed, for example by using an etching or ultraviolet laser heating technique. After exposure of regions 1201, suitable light conversion layers 1501 are applied as described above. Additionally, index matching layers, protective layers, and contact structures are applied as described above.

As will be understood by those familiar with the art, the present invention may be embodied in other specific forms without departing from the spirit or essential characteristics thereof. Accordingly, the disclosures and descriptions herein are intended to be illustrative, but not limiting, of the scope of the invention which is set forth in the
5 following claims.

10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221
2222
2223
2224
2225
2226
2227
2228
2229
2230
2231
2232
2